



Ovation SP-300CW

Ovation SP-300CW is a quiet, medium throw LED powered followspot that projects a crisp cool white beam. On board manual dimming and a full-blackout iris are standard for beam control along with smooth manual sliders for zoom and focus to adjust from a spot to a flood. A 6-slot manual boomerang is attached to the front of the unit to add your favorite gel colors and provide quiet color changing.



AT A GLANCE

- High power LED followspot with stand for mid-sized venues
- 5,500 K cool white spot with 10° to 20° zoom
- Full blackout, 24-leaf iris
- Manual linear dimmer
- 6-position, removable color changer
- Virtually silent operation for use in studio and theatre applications
- Easy access hatch for cleaning optics

Specifications

Optical

- Light Source: 1 LEDs (CW) 260 W, (3.6 A), 5,524 K, 50,000 hours life expectancy
- Color Temperature (at full): 5524 K
- CRI: 88
- Beam Angle: 10° to 14°
- Field Angle: 10° to 18°
- Zoom Angle: 10° to 18°
- Lumens (9°): 6,401
- Lumens (17°): 6,453
- Illuminance (Narrow): 18,557 lux @ 5 m
- Illuminance (Wide): 9,271 lux @ 5 m
- PWM Frequency: 2300 Hz

Dynamic Effects

- Colors: 6 + white
- Dimmer: Manual, Linear
- Zoom: Manual
- Focus: Manual
- Iris: 24-leaf, full blackout

Construction / Physical

- Dimensions: 46.8 x 13.98 x 15.55 in (1,150 x 355 x 395 mm)
- Dimensions (shipping size): 51.18 x 25.98 x 17.71 in (1,300 x 660 x 450 mm)
- Dimensions (Stand with fixture, optimal open): 46.8 x 13.98 x 62.4 in (1,189 x 355 x 1,585 mm)
- Diameter (Stand with fixture, optimal open): 33.8 in (stand) 52.8 in (fixture)
- Dimensions (Stand with fixture, max Open): 46.8 x 13.98 x 81.6 in (1,189 x 355 x 2,073 mm)
- Diameter (Stand with fixture, max open): 39.6 in (stand) 52.8 in (fixture)
- Weight: 49 lb (22.2 kg)
- Weight (shipping weight): 123.45 lb (56 kg)
- Exterior Color: Black
- Housing Material: Steel

Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon (powerCON Compatible)
- Power Input: Seetronic Powerkon (powerCON Compatible)
- Cable Length (power): 5 ft (1.5 m)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 249 W, 2.08 A @ 120 V, 60 Hz
- Power and Current: 258 W, 1.22 A @ 208 V, 60 Hz
- Power and Current: 260 W, 1.10 A @ 230 V, 50 Hz
- Power and Current (resting): 19 W, 0.15 A @ 120 V, 60 Hz
- Power and Current (resting): 40 W, 0.19 A @ 208 V, 60 Hz
- Power and Current (resting): 40 W, 0.16 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET, FCC

- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- Ovation SP-300CW
- Seetronic Powerkon IP65 power cord
- Tripod stand
- Starter pack of gels