


# WELL Gobo



## SPECIFICATIONS

### Optical

- Light Source: 1 LED (CW) 25.2 W, (1.3 A), 6542 K, 50,000 hours life expectancy.
- Color Temperature (at full): 6542 K
- Lumens: 2892
- CRI: 79.1
- Beam Angle: 17.3° to 36.6°
- Field Angle: 20° to 41°
- Zoom Angle: 20° to 41°
- Illuminance (17.3°): 1,487 lux @ 5 m
- Illuminance (8 hr mode 17.3°): 1,487 lux @ 5 m
- Illuminance (36°): 347 lux @ 5 m
- Illuminance (P/S mode 36°): 165 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

### Dynamic Effects

- Manual Tilt: 180°
- Tilt Ranges: 0° to 180° tilt
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Manual
- Focus: Manual
- Strobe Rate: 0 to 25 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

## FEATURES

- A completely wireless, IP 65 rated, battery powered Gobo Projector with a cool white LED and manual framing shutters that is controlled by W-DMX, IR remote (not included), or manually from the OLED display
- Zoom range of 20° to 41° making sizing patterns on surfaces easy
- Hard and soft focuses are easily achieved
- Works with both glass and metal E size gobos (1 mm max thickness)
- User selectable PWM settings to ensure flawless on camera operation
- M12 hole for easy clamp installation
- Up to 8 hours of operational time on full charge
- Recharging case can be power linked to save on power outlets
- Recharging case can be charged with the lid closed saving warehouse space

## Construction / Physical

- Dimensions (Single Unit): 10.11 x 6.81 x 12 in (257 x 173 x 305 mm)
- Dimension (Charging Case): 27.64 x 17.24 x 23.36 in (702mm x 438 x 593.4 mm)
- Weight (Single Unit): 6.6 lb (3 kg)
- Weight (Charging Case): 71 lb (32.21 kg)
- Exterior Color: Black
- Housing Material (Single Unit): Aluminum diecast
- Housing Material (Charging Case): Aluminum alloy, wood
- Gobo Size (Optional): "E": 37.5 mm (outside), 24 mm (image), 1 mm (max. thickness)

## Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon
- Power Input: Seetronic Powerkon
- Cable Length (power): 5 ft (1.5 m)

## Control

- Control Protocol: W-DMX, IRC
- DMX Channels: 1, 2, 3 or 6

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 9 units @ 120 V; 15 units @ 208 V; 16 units @ 230 V
- Power and Current (single unit charging): 42 W, .345 A @ 120 V, 60 Hz
- Power and Current (charging case): 168 W, 1.38 A @ 120 V, 60 Hz
- Power and Current (single unit charging): 48 W, 0.220 A @ 208 V, 60 Hz
- Power and Current (charging case): 192 W, 0.880 A @ 208 V, 60 Hz
- Power and Current (single unit charging): 49 W, 0.211 A @ 230 V, 50 Hz
- Power and Current (charging case): 196 W, 0.844 A @ 230 V, 50 Hz

## Certifications / Qualifications

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use

## What's Included

- (4) WELL Gobo
- Charging Case
- powerCON power cable with Edison plug
- (4) Gobo holder